

# 차단기 용량별 Accura 2350 선정

\* LS MCCB Type

AF		30AF		50AF			60AF	
Type		E-Type	S-Type	N-Type	S-Type	H-Type	N-Type	S-Type
극수	2	ABE32b	ABS32c	ABN52c	ABS52c	ABH52c	ABN62c	ABS62c
	3	ABE33b	ABS33c	ABN53c	ABS53c	ABH53c	ABN63c	ABS63c
	4		ABS34c	ABN54c	ABS54c	ABH54c	ABN64c	ABS64c
정격전류	A	(3,5,10),15,20,30		15,20,30,40,50			15,20,30,40,50,60	
정격차단 전류	425/460	2.5	14	14	18	50	14	18
	380	2.5	18	18	22	50	18	22
	220/250	5	30	30	35	100	30	35
외형치수	3극 (W)	75		75			75	
	2극 (W)	50		50			50	
Accura 2350	3P(SC)	60A-75		60A-75			60A-75	
	1P(SC)	60A-50		60A-50			60A-50	

AF		100AF		125AF		250AF		
Type		N-Type		S-Type	H-Type	N-Type	S-Type	H-Type
극수	2	ABN102c	ABN102d	ABS102c	ABH102c	ABN202c	ABS202c	ABH202c
	3	ABN103c	ABN103d	ABS103c	ABH103c	ABN203c	ABS203c	ABH203c
	4	ABN104c	ABN104d	ABS104c	ABH104c	ABN204c	ABS204c	ABH204c
정격전류	A	15,~,75,100		15,~,100,125		100,125,150,175,200,225,250		
정격차단 전류	425/460	18	26	37	50	26	37	50
	380	22	30	42	50	30	42	50
	220/250	35	50	85	100	65	85	100
외형치수	3극 (W)	75		90		105		
	2극 (W)	50		60		105		
Accura 2350	3P(SC)	100A-75		125A-90		250A-105		
	1P(SC)	100A-50		125A-60		250A-105		

\* 현대 MCCB UCB Type

AF		50AF			125AF			
Type		R-Type	H-Type	L-Type	R-Type	S-Type	H-Type	L-Type
외형치수	3극 (W)	90	90		90		90	
	2극 (W)	60	90		60		90	
Accura 2350	3P(SC)	125A-90	125A-90		125A-90		125A-90	
	1P(SC)	125A-60			125A-60			

\*현대 MCCB UAB Type 상부 LS MCCB 램 동일 선정

**\*125AF 이하 H-Type은 3P(SC)일 경우 무조건 사이즈 125A-90**